



ate plastic bowl Acetaldehyde

Chlorobenzene

Methylene Chloride

Acetic acid (conc.)

Acetone

Acrylonitrile

Ammonia

Ammonium fluoride

Ammonium hydroxide

Ammonium sulfide

Anaerobic adhesives
and sealants

Antifreeze

Benzene

Benzoic acid

Benzyl alcohol

Chloroform

Cresol

Cyclohexanol

Cyclohexanone

Cyclohexene

Dimethyl formamide

Dioxane

Ethane tetrachloride

Ethyl acetate

Ethyl ether

Ethylamine

Ethylene chlorohydrin

Ethylene dichloride

Methylene salicylate

Milk of lime (CaOH)

Nitric acid (conc.)

Nitrobenzene

Nitrocellulose lacquer

Phenol

Phosphorous hydroxide
chloride

Phosphorous trichloride

Propionic acid

Pyridine

Sodium hydroxide

Sodium sulfide

INSTALLATION

1. Refer to the warning.
2. Install downstream of dryer or where required.
3. Install the unit with the airflow in direction of arrow.
4. Silica gel changes from dark blue to pink to indicate 10% relative humidity, reactivating itself when dry air flows through unit.

MAINTENANCE

1. Under normal conditions this unit will be trouble free with no maintenance required.
2. The silica gel will require changing if oil or other contamination enters the unit.