

## WARNING

To avoid unpredictable system behavior that can cause personal injury and property damage:

- Disconnect electrical supply (when necessary) before installation, servicing, or conversion.
- Disconnect air supply and depressurize all air lines connected to this product before installation, servicing, or conversion.
- Operate within the manufacturer's specified pressure, temperature, and other conditions listed in these instructions.
- Medium must be moisture-free if ambient temperature is below freezing.
- Service according to procedures listed in these instructions.
- Installation, service, and conversion of these products must be performed by knowledgeable personnel who understand how pneumatic products are to be applied.
- After installation, servicing, or conversion, air and electrical supplies (when necessary) should be connected and the product tested for proper function and leakage. If audible leakage is present, or the product does not operate properly, do not put into use.
- Warnings and specifications on the product should not be covered by paint, etc. If masking is not possible, contact your local representative for replacement labels.










## INSTALLATION

1. A I G, 300, (21, )
2. 32 F, 150 F, (0 C, 66 C).
- 3.
- 4.
5. A
6. A 1/4" 1/4"
- 7.

## MAINTENANCE

1. A
2. DI A E BLE: B
3. A E BLE: E A I G I G BE F LL EA ED I G E.
4. IF I ILL EG LA E E E EDED, IF E E D BEC E E CE IE: O

## REPAIR KITS AND REPLACEMENT PARTS

	.....	RRP-95-159
	(0-180, )	RRP-95-220
	(0-125, )	RRP-95-226
	(0-160, )	K4520N14160
	(0-300, )	K4520N14300
	.....	RRP-95-451
	.....	GRP-95-734



**Las Instrucciones de la instalación  
y el Servicio**

**84-007-000 (Spanish)**

**Regulador Modelo R30  
con Variaciones y Accesorios**

**PUBLICADO: April, 2006**

**Desbancan: Julio, 2004**

**Doc.# 84007000, ECN# 060299, Rev. 5**

